

L0410N3M | 贵金属电刷 Precious Metal Commutation


应用领域：微型无人机、智能电玩、小家电产品等领域。

Applications: mini UAV's, remote control hobby products, small household appliances, etc.

主要技术指标 | Characteristics

			30-320-3.0	02-820-3.0
1	电压	Voltage	V	3.0
2	端电阻	Terminal resistance	Ω	45
3	空载转速	No-load speed	rpm	32000
4	空载电流	No-load current	mA	15
5	堵转转矩	Stall torque	mNm	0.04
6	堵转电流	Stall current	mA	67
7	负载转矩	Load torque	mNm	0.01
8	负载转速	Load speed	rpm	23110
9	负载电流	Load current	mA	30
10	最大输出功率	Max. output power	W	0.03
11	最大效率	Max. efficiency	%	27.8
12	反电势常数	Back-EMF constant	mV/rpm	0.07
13	转矩常数	Torque constant	mNm/A	0.69
14	转速 / 转矩斜率	Speed/torque gradient	rpm/mNm	888889
15	转子惯量	Rotor inertia	gcm ²	0.004
16	重量	Weight	g	0.6
17	工作温度范围	Operating temperature range	$^{\circ}\text{C}$	-20~+65

特性曲线 | Characteristics Curve



可选参数 | Options

导线长度 Lead wires length
轴长 Shaft length
性能 Special coils
齿轮箱 Gearheads

外观图 | Outline Drawing

