

BO4840NH2B | 外转子带传感器 Outer Rotor, Sensored

应用领域：无人机、工业设备等精密驱动领域。

Applications: UAV, industrial automation, etc.

主要技术指标 | Characteristics

			01-105-18.0	02-105-24.0	03-105-36.0	
1	电压	Voltage	V	18.0	24.0	36.0
2	端电阻	Terminal resistance	Ω	0.034	0.053	0.11
3	空载转速	No-load speed	rpm	10500	10500	10500
4	空载电流	No-load current	A	1.6	1.2	0.9
5	堵转转矩	Stall torque	mNm	8614	9831	10656
6	堵转电流	Stall current	A	529.4	452.8	327.3
7	额定转矩	Nominal torque	mNm	423	427	420
8	额定转速	Nominal speed	rpm	9350	9400	9440
9	额定电流	Nominal current	A	25.7	19.5	12.9
10	最大输出功率	Max. output power	W	2367	2701	2928
11	最大效率	Max. efficiency	%	89.2	89.9	89.7
12	反电势常数	Back-EMF constant	mV/rpm	1.7	2.3	3.4
13	转矩常数	Torque constant	mNm/A	16.3	21.8	32.7
14	KV 值	KV Value	rpm/V	583	437.5	292.0
15	转速 / 转矩斜率	Speed/torque gradient	rpm/mNm	1.22	1.07	0.99
16	转子惯量	Rotor inertia	gcm ²	398	398	398
17	重量	Weight	g	267	267	267
18	热阻 (机壳 - 环境)	Thermal resistance housing-ambient	K/W		0.9	
19	热阻 (线圈 - 机壳)	Thermal resistance winding-housing	K/W		1.0	
20	热时常数 (电机)	Thermal time constant motor	s		300	
21	热时常数 (线圈)	Thermal time constant winding	s		60	
22	工作温度范围	Operating temperature range	°C		-40~+120	
23	绕组耐温等级	Thermal class of winding	°C		180	
24	轴向间隙	Axial play	mm		0.012	
25	径向间隙	Radial play	mm		0.008	
26	动态轴向载荷	Axial load dynamic	N		10	
27	静态轴向载荷	Axial load static	N		110	
28	径向载荷 (距安装面 3mm)	Radial load at 3 mm from mounting face	N		42	
29	极对数	No. of pole pairs			7	
30	轴承	Bearings			2 枚滚动轴承/2 ball bearings	
31	换向结构	Commutation			霍尔传感器/Hall Sensor	
32	防护等级	Protection class			IP 20	

★可选参数 Options: 导线长度 Lead wires length 轴长 Shaft length 性能 Special coils 齿轮箱 Gearheads 轴承 Bearing type

编码器 Encoder 驱动器 Driver

外观图 | Outline Drawing

